

Product datasheet

Special Design – Designer doors lacquer New Amsterdam – Design by Piet Boon



Product information

Modern panel door with a factory finished surface. New Amsterdam doors are manufactured in our factory where modern technology is combined with traditional craftsmanship.

The doors are designed for rooms with relative humidity of 30% - 55%.

The New Amsterdam doors are supplied together with one of the Bod'or doorframes, sliding systems or pivot systems.

Door systems

Cube interior doors are supplied together with one of the following doorframe systems, sliding systems or pivot system..

Cube Doorframe: Cube on the wall, Cube flush with the wall with 6 mm or 12 mm shadow gap (also reverse) , Cube SF, Undercover 25 (also Reverse)

Sliding system: Nixx, Ceiling, Tube Front, RAIL RIT, Cube in the wall

Pivot System TURN

Hardware

New Amsterdam doors are supplied including all hardware depending on the chosen door system

Hinged door with Cube frame including mounted magnetic lock as standard

Surface finish

Premium Silk Lacquer Basis (RAL 9001/ RAL 9010/ RAL 9016) or Color Collection

Premium Silk Lacquer other colours RAL/ NCS/ Sikkens

Supermatt Basis (black or white) or Color Collection

All available finishes can be found on <https://www.bodor.eu/collection/special-design/>

Door height

Minimum and maximum door height is depending on chosen door system.

Hinged doors up to 3000 mm door height as a standard

Door width

Minimum and maximum door width is depending on chosen door system.

Hinged doors up to 1235 mm door width as a standard

Handing hinged doors

Standard

Reverse, opening inwards (not possible with Cube SF)

See drawing handing hinged doors.

Installation

See installation manual and installation video

Care instructions

See *care instructions Bod'or doors*

