

Datasheet

Pocket system incl. Cube frame



Sliding system running in the wall with cube frame on the wall or frame flush with the wall

Assembly

Ceiling or lintel attachment. When mounted in the wall and 40 mm thick door leaf should wall pocket be at least 50 mm

The maximum wall opening width is 1,100 mm

Sliding door dimensions

sliding door width

Sliding door is calculated similarly to hinged doors according to the dimension table.
Dimension of hinged door = dimension of sliding door.

Sliding door height

Sliding door is calculated similarly to hinged doors according to the dimension table.
Dimension of hinged door = dimension sliding door.

The maximum door leaf weight for Cube in the wall is 80 kg.

Rail length

1-leaf	2 x door leaf width
2-leaf	2 x total door leaf width

Application

Sliding system can be delivered in connection with the following doors:

- Cube Basis Cube Lacquer / Cube Finline / Pure / RAW Oak
- Cube Lines Cube Lacquer / Cube CUT / Design Lacquer / Design Pure
- Transparency Lumia / Vision / Design Lack
- Special design

Door leaf is supplied with a groove for floor guidance

optional

Soft stop / damping system

Parts list

Track profile

Accessory set in a separate box (includes carriages, stoppers and screw-on door leaf holder)
bracket for wall mounting

